



PARALLEL SHAFT HELICAL GEARBOX

Center Distance	: Up to 850 mm
Ratio	: 6.3:1 to 315:1
Torque	: up to 49000 N.m
Input power	: 5 Hp to 100 Hp
Mounting	: foot
Output shaft	: 45 mm to 120 mm

NXU WORM SPEED REDUCTION GEARBOX

Center Distance	: 1.75" inch to 14" inch
Ratio	: 10:1 to 70:1
Torque	: up to 10000 N.m
Input power	: 0.5 Hp to 40 Hp
Mounting	: foot /vertical



F SERIES HELICAL GEARBOX

Model	: F37,F47,F57,F67,F87,F97,F107
Ratio	: 10:1 to 150:1
Torque	: 2500 N.m
Input power	: 0.5 Hp to 10 Hp
Mounting	: Foot /Vertical
Output hollow	: 30 mm to 60 mm

WPA SERIES GEARBOX

Center Distance	: 50 to 155 mm
Ratio	: 7.5:1 to 80:1
Torque	: 3700 N.m
Input power	: 0.5 Hp to 40 Hp
Mounting	: Foot /Vertical





INLINE HELICAL GEARBOX

Ratio	:	5:1 to 200:1
Torque	:	up to 20000
Input power	:	0.25 Hp to 12.5 Hp
Mounting	:	Foot /Vertical

NMRV GEARBOX

Center Distance	:	up to 150 mm
Ratio	:	7.5:1 to 100:1
Torque	:	up to 250 N.m
Input power	:	0.16 Hp to 7.5 Hp
Mounting	:	Universal mounting
Output shaft	:	Hollow 14 mm - 50 mm



PLANETARY GEARBOX

Ratio	:	3.26 Onwards
Torque	:	25000 N.m
Input power	:	0.25 Hp to 150 Hp hydraulic motor,servo motor
Mounting	:	foot flange agitator and special mounting
Output shaft	:	solid / hollow

K SERIES GEARBOX

Ratio	:	10:1 TO 120:1
Torque	:	up to 8000 N.m
Input power	:	1 Hp to 50 Hp
Mounting	:	Universal mounting
Output shaft	:	40 mm to 90 mm



CYCLOID GEARBOX

Model	:	JXJ0,JX1,JX2,JX3,JX4
Ratio	:	11:1,17:1,23:1,29:1,43:1,59:1
Output shaft	:	25mm to 55mm
Input power	:	0.5 Hp to 10 Hp
Mounting	:	horizontal & vertical